

Kart Technical Exception Class Approval

Ref: **KTE-2012-127**

The MSA can confirm that 210 Challenge / ABkC has been granted permission to run the 210 National Class in the UK. Class Regulations will be reviewed by the MSA on a yearly basis.

Details:

Class Regulations as attached.

Date Approved: 16 December 2011

MSA Stamp & Signature:



JOE HICKERTON
MSA Technical Administrator

210.0	Group	Senior (Gearbox)
210.1	Class	210 National
	Affiliation	210 Challenge

210.2 Introduction. This class will be part of the 210 Challenge and since 1.1.97 has been administered by the 210 Challenge co-ordinator. The class regulations are not expected to change except for silencing requirements. References to Section U refer to the MSA Competitors' and Officials' Yearbook.

210.3 Chassis. In accordance with MSA Competitors' and Officials' Yearbook regulations.

210.3.1 Bodywork: Bodywork and/or front fairing are not mandatory in this class.

210.3.2 Front, rear and side protection is mandatory and must comply with the MSA Competitors' and Officials' Yearbook with the following exceptions:

210.3.3 Unless a front fairing is fitted conforming to Section U, the front bumper must conform to U17.12. In Long Circuit racing trim, it must conform to U17.12.2.

210.3.4 Unless bodywork is fitted conforming to Section U, side bumpers are mandatory and must conform to U17.15-17.17.

210.3.5 In the case of a "Wet Race" side bumpers or bodywork may not be located outside the plane passing through the outer edge of the rear wheels.

210.3.6 Bubble shields conforming to U17.22 are permitted.

210.3.7 Floortrays are permitted to extend rearwards beyond the central strut of the chassis frame as for karts in Long Circuit trim as defined in U16.6.

210.3.8 Rear bumper must be fitted in accordance with U17.13.

210.4 Engine. Maximum 210cc. This class is for the Villiers 9E engine and associated models, together with modern replicas of that engine. The engine will consist of a single cylinder air-cooled two-stroke with gearbox mounted in unit. The engine shall be piston timed with a single carburettor. The ignition system shall be free in accordance with Appendix 4 D.3. The stroke shall be 72mm and the maximum bore 60.9mm. The engine shall be equipped with a single sparking plug. The maximum diameter of the cylinder barrel fins shall not exceed 160mm and the barrel shall have at least eight fins. The overall height of the cylinder barrel between flange faces shall be between 128mm and 133mm, including any spacers or gaskets. The maximum diameter of the cylinder head shall not exceed 160mm and the height of the cylinder head shall not exceed 76mm. The head shall have at least eight vertical fins. The gearbox casing shall be of identical appearance to the original Villiers 9E, 10E or 11E pattern. The exhaust outlet must take an exhaust pipe not larger than 1.75in OD. The engine mounting points to be as the original pattern and the contours of the crankcase to conform with the original Villiers outline. Reed valve induction is permitted, providing that the original position of the induction pipe is retained, and that the valve is only fitted in the induction tract. Reverse barrel permitted. The barrel retaining stud centres must remain in the original 9E, 10E and 11E positions and be on the original 70mm centres. All systems of injection and/or spraying of products other than fuel are forbidden.

210.5 Transmission. Maximum of four operative gears.

210.6 Brakes. In accordance with U16.10.

210.7 Tyres.

Slick: Dunlop SL3 front, 10 x 4.5 x 5 and rear 11 x 7.1 x 5.

Wet: Dunlop KT5 or KT6 or KT8, KT10 or KT11, front 10 x 4.0 x 5 and rear 11 x 6.5 x 5.

Only complete sets of KT5 or KT6 or KT8, KT10 or KT11 may be used.

210.8 General.

210.8.1 Weight. Minimum weight with driver on the completion of any part of the event 190kg long circuit trim and 185kg short circuit trim

210.8.2 Plates. Red number plates with white numbers. U17.27 applies.

210.8.3 Age. The class is open to any driver aged 16 or over on short or long circuits. A junior may transfer to the class at any time during the year that he or she attains their sixteenth birthday, provided that they have previously competed in Junior Gearbox and hold a minimum of a National A licence.

210.8.5.1 Intake Silencing. See Appendix 3.

210.8.5.2 Exhaust Silencing. See Appendix 3.

210.9 Notes.

210.9.1 ABk/BSA rules (which must be read in conjunction with the above).

210.9.1.1 Chassis. All chassis main parts must be firmly secured together or to the chassis frame. Flexible connections are only authorised for the conventional steering knuckle support, and for the steering system. All other devices with the function of one, two or three dimensional joints are forbidden. The chassis frame is the central and main supporting element of the entire vehicle. It must have the necessary strength in order to be able to absorb the loads which are produced when the vehicle is in motion. Any hydraulic, pneumatic or elastomeric elements for damping chassis oscillation are forbidden.

Approved by MSA on KTE-2012-127